

Class 29: Diesel Electric Locomotive




Map of Malaysia




Class 29: Diesel Electric Locomotives

Specifications

•		
Power system		Diesel Engine
Axle load		19,400 kg
Gauge		1,000 mm
Axle arrangement		Co' Co'
Total mass		116.4 tons (19.4tons×6axles)
Maximum speed		120 km/h
Engine power		2,580 kW
Starting tractive effort		410 kN
Maximum electric braking effort		220 kN
Ambient temperature		-10 to 39 ℃
Traction motors		6 × AC Motors
Dimensions	Overall length	20,668 mm
	Maximum width	2,800 mm
	Height	3,875 mm





Class 29 Locomotive

Find out more on http://toshiba-railway.com

TOSHIBA CORPORATION Social Infrastructure Systems Company

1-1, Shibaura 1-Chome, Minato-ku, Tokyo 105-8001, JAPAN Tel: +81-(0)3-3457-4556

- The information contained herein is as of August 1, 2012.
- •The information contained herein is subject to change without notice.

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.

 TOSHIBA products should not be embedded to the downstream products which are prohibited to be produced and sold, under any law and regulations.

 TOSHIBA does not take any responsibility for incidental damage (including loss of business profit, business interruption, loss of business information, and other pecuniary damage) arising out of the use or disability to use TOSHIBA products.
- •The products described in this document may include products subject to the foreign exchange and foreign trade laws.
- The products described in this document may contain components made in the United States and subject to export control of the U.S. authorities. Diversion contrary to the U.S. law is prohibited.